

- BLAZING LINE SPEEDS
- SOLID STATE ELECTRONICS
- VARIABLE SPEED LINE CONTROL



VMX3.5

3,500 LB Capacity
(1588 kg)
PN: 76-72112



VMX2.5

2,500 LB Capacity
(1134 kg)
PN: 76-72105

Mile Marker's new, completely redesigned ATV/UTV winches provide premium performance in line speed and braking. The new platform will better accommodate mounting systems with its center focused drum, and with MiFi Technology, you can experience the precision and safety of variable speed control without any of the moving parts of traditional solenoids.

PRODUCT FEATURES:

- Potent Permanent Magnet Motor
- Redesigned Braking Mechanism
- Center Focused Drum
- Automatic Load holding brake
- Includes Roller Fairlead
- Includes Both Illuminated Remote Control and Illuminated Handlebar Remote Control



VMX3.5 PRODUCT SPECIFICATIONS:

Part Number	76-72112
Rated line pull	3500 lbs (1588 kg) Single Line
Gear Train	3 Stage Planetary
Gear Ratio	153:1
Motor	Permanent Magnet, 2 hp (1.5kw), 12 V DC
Control Pendant	Infinite Speed Joystick Remote, 12' (3.7 m)
Dimensions (LxWxH)	13.0" X 4.18" X 4.3" (330 mm X 106.2 mm X 109.2 mm)
Cable	7/32" X 50' (nominal 5,600 lbs, 2540 kg) (5.45 mm X 45.2 m)
Drum Size:	1.5" X 3.15" (38.1 mm X 80 mm)
Net weight	25 lbs (11.3 Kgs)
Bolt Pattern	4 Bolt Pattern, 4.88" X 3", (124 mm X 76.2 mm)

VMX2.5 PRODUCT SPECIFICATIONS:

Part Number	76-72105
Rated line pull	2500 lbs (1134 kg) Single Line
Gear Train	3 Stage Planetary
Gear Ratio	241:1
Motor	Permanent Magnet, 2 hp (1.5kw), 12 V DC
Control Pendant	Infinite Speed Joystick Remote, 12' (3.7 m)
Dimensions (LxWxH)	13.0" X 4.18" X 4.3" (330 mm X 106.2 mm X 109.2 mm)
Cable	3/16" X 50' (nominal 4200 lbs, 1905 kg) (4.8 mm X 15.2 m)
Drum Size:	2" X 3.15" (50.8 mm X 80 mm)
Net weight	24.2 lbs (11 Kgs)
Bolt Pattern	4 Bolt Pattern, 4.88" X 3", (124 mm X 76.2 mm)

VMX3.5 PERFORMANCE:

LINE PULL	LINE SPEED	MOTOR CURRENT		
lb	kg	fpm	mpm	amps @ 12 V
0	0	19	5.8	43
500	227	16.2	4.9	62
1000	454	14.4	4.4	95
1500	680	13	3.9	110
2000	907	11.7	3.6	130
2500	1134	10.8	3.3	140
3000	1360	10.2	3.1	152
3500	1588	9.8	2.9	160

VMX2.5 PERFORMANCE:

LINE PULL	LINE SPEED	MOTOR CURRENT		
lb	kg	fpm	mpm	amps @ 12 V
0	0	24	7.3	41
500	227	21.8	6.64	70
1000	454	17.1	5.2	100
2000	907	10.9	3.32	175
2500	1134	7.5	2.28	212

